



ITALTOWER®
HEAVY DUTY LIGHTING TOWERS

ASTRID PRO02-EVO



Picture for illustration purpose only.

Floodlight	Lumen	Light coverage
6x150W LED	120.000 lm	4300 sqm

Italtower Srl

Via Meucci 5-11, 35028

Pieve di Sacco (PD) – Italy

P.Iva 04725890281

www.italtower.com

info@italtower.com





Technical Specification

Rated frequency	50 Hz
Rated Voltage	230 V
Rated Power	0.7 Kw
Operating temperature	-40/+50
Sound Level	61 dB
Control unit	DeepSea 3110
Auxiliary power	2 kVA

Engine

Model	Kohler KDW 702
Speed	1500 rpm
Coolant	Liquid
Cylinders	2
Emissions	Stage V

Alternator

Model	Linz Alumen
Rated outlet	3.5 kVA

Energy consumption

Fuel consumption	0,55 l/h
Tank	110 l
Fuel	Diesel
Running time	200 h

Galvanized mast

Height	8.5 m
Mast	Hydraulic
Rotation	355 °
Wind speed resistance	110 km/h

Canopy & Trailer

Trailer	Road – tow trailer EU approved
Tyres	185/70/R13
Basement	Bunded base 110%
Stabilizers	4 + 1 (wheel)
Canopy	Powder coating paint

Optional

Optional included as standard	Dusk to dawn sensor with Autostart AMOSS kit (trailer security system)
-------------------------------	---------------------------------------------------------------------------

Shipment

Dimension	235x147x240 cm
Weight	850 kg
Truck	10 units
Container 40''	11 units

